



Luxury Vinyl Plank
Range Collection
SPC Click

Specification Sheet

Classification: ASTM F 1700-04 Class III Type B Solid Vinyl Flooring

Size:

7" x 48" **7.56" x 48.43" (3 SKU'S)**
Range Briarwood Range Country Cabin
Range Fallen Timber

9" x 60" **9.45" x 59.84" (5 SKU'S):**
Range Basecamp Range Chesapeake
Range Switchback Range Trailhead
Range Woodland Trail

Total Thickness: 5mm (4mm + 1mm IXPE Acoustical Backing)

Wear Layer Thickness: 22 mil / 0.55mm, UV coated with ceramic bead & Vanquish Organic anti-microbial/anti-bacterial

Construction: Layered - consisting of wear layer, film, core and backing

Edge: Four-Sided Micro-Bevel

Total # of SKU's: 8 colors

Limited Warranty: Lifetime Residential, 20 Year Commercial

Recycled Content: 100% Virgin Materials. Product can be recycled post-use

Packaging:

7" x 48"
(Actual Size 7.56" x 48.43")
10 pieces / carton
23.769 SF / carton
55 cartons / pallet
23 pallets / container

9" x 60"
(Actual Size 9.45" x 59.84")
8 pieces / Carton
29.922 SF / carton
48 cartons / pallet
21 pallets / container



Product Testing:

Flammability:	ASTM D 2859-06 / CPSC FF 1-70	Passed
Critical Radiant Flux:	ASTM E 648-06	Class I, CRF > 0.45
Smoke Density:	ASTM E 662-06	Pass (< 450)
Slip Resistance:	ASTM D 2047	Pass (Dry >0.8)
Stain Resistance:	ASTM F 925	Pass
Heat Stability:	ASTM F 1514	Pass
Light Stability:	ASTM F 1515	Pass
Abrasion Resistance:	ASTM D 4060	Pass - 35000 cycles
Dimensional Stability:	ASTM F 2199	Pass
Static Load Test:	ASTM F 970	Pass - 1300 PSI
Impact Insulation (IIC):	ASTM E 429-09	51 dB w/ 6" concrete
Delta IIC:	ASTM E 2179-09	23 dB w/ 6" concrete
Residual Indentation:	ASTM F 1914	Pass (1%)
Phthalate Content:	EN 14372	Not Detected
Sound Isolation (IIC):	ASTM E 989	>50 dB

